

### DESCRIPTION:

CoreTect 348 Low VOC Asphalt Primer is a blend of specially processed asphalt and petroleum solvents that, when properly applied, cure to a hard protective shell on masonry, metal, concrete or weathered asphaltic substrates, providing an exceptional adhesive base for the attachment of roofing membranes, insulations, flashings and adhesives.

### USES:

CoreTect 348 Low VOC Asphalt Primer is designed as a fast-curing prime coat for application over a variety of construction substrates over which roofing and waterproofing membranes, BUR systems or asphaltic adhesives and coatings will be applied. CoreTect 348 can also be used to prime and rejuvenate old or weathered asphalt surfaces prior to the application of new asphaltic membranes or coatings. Unlike many Low VOC asphalt primers, CoreTect 348 utilizes a specially refined asphalt that cures to a hard surface, yet is highly fluid and easily applied, even in cooler temperatures.

### APPLICATION:

CoreTect 348 Low VOC Asphalt Primer can be easily applied with a brush, roller or spray equipment at the rate of 0.5 – 1.0 gallon/100 sq. ft., depending upon the absorbency and temperature of the substrate. Highly porous surfaces such as a cinder block or concrete may require two applications. Regardless of the substrate, all surfaces must be clean, dry and free of oil, grease or foreign matter. DO NOT THIN this product with additional solvents or fuels. The average cure time for CoreTect 348 is 3-4 hours, depending upon ambient conditions.

### PHYSICAL PROPERTIES:

Physical Properties	Typical Value	Standard
Flash Point, °F	> 104	ASTM D93
Viscosity, Saybolt Fural @ 77°F, seconds	<125	ASTM D41 / Type I
Penetration on Residue @ 77°F, dmm	20	ASTM D5
Density (Water = 1)	0.95	ASTM D6511
% of Solids by Weight	64	ASTM D6511
VOC Content, grams/liter	348	ASTM D3960

### PACKAGING:

CoreTect 348 is available in 5 gallon pails (18.9L); Net Contents 4.75 gallons (17.9L)

The physical properties shown are based upon average test results and are subject to variance, however, VOC content is listed as a maximum value, and will not exceed 250 grams/liter. This product is for commercial, industrial use only, and for the desired performance results, it is critical that the product be applied by a professional in accordance with proper and accepted industry practice. Please refer to SDS for additional handling and disposal instructions.

DISCLAIMER and LIMITED WARRANTY: This product is not warranted to be suitable for any purpose other than the general purpose for which it is intended. The product is warranted to be of merchantable quality when used in accordance with the instructions hereon, and liability under this warranty is limited to replacement of the product if found to be defective, or at the option of the Seller, to refund the purchase price. In the event of a claim under this warranty, notice must be given to the Seller in writing. This warranty is issued and accepted in lieu of all other expressed warranties and expressly excludes liability for consequential damages.